

Soft Mount Washer Extractor

MSM15 MSM23 MSM30 MSM50
MSM70 MSM100 MSM150



- Suspension system with springs and shock absorbers
- SS304 Stainless steel basket and outer drum
- Frequency inverter drive
- High extraction speeds up to 300G
- Programmable computer up to 30 wash programs
- Programmable water levels, temperatures and cool-down
- Direct steam injection heating
- Safety door interlock system
- Stainless steel panels
- Flushable five compartment dry supply injector (Three compartment on the MSM15/23)
- Five liquid supply injection points
- Wide, rugged doors with silicone door seal
- Built-in bearing lubrication system
- Emergency manual override controls (Except MSM15/23/150)

Technical Specification:

	MSM15	MSM23	MSM30	MSM50	MSM70	MSM100	MSM150
Rated Capacity	15kg	23kg	30kg	50kg	70kg	100kg	150kg
Basket Volume	149L	234L	320L	544L	708L	1014L	1540L
Basket Diameter	650mm	750mm	902mm	1069mm	1200mm	1240mm	1460mm
Basket Depth	450mm	530mm	500mm	606mm	626mm	840mm	920mm
Door Opening Diameter	381mm	381mm	467mm	513mm	632mm	632mm	739mm
Motor	2.2kw	3kw	4kw	5.5kw	7.5kw	11kw	22kw
Inverter	3.7kw	3.7kw	5.5kw	7.5kw	11kw	15kw	22kw
High Extract G-Force	300G	300G	300G	300G	300G	300G	300G
Water Inlet	DN20	DN20	DN25	DN40	DN40	DN40	DN50
Steam Inlet	DN20	DN20	DN20	DN25	DN25	DN25	DN40
Drain Connection	DN76	DN76	DN150	DN150	DN150	DN150	DN150
Compressed Air	8mm	8mm	8mm	8mm	8mm	8mm	8mm
Height	1590mm	1665mm	1960mm	2080mm	2310mm	2310mm	2850mm
Width	1015mm	1075mm	1483mm	1723mm	1833mm	1833mm	2170mm
Depth	1323mm	1400mm	1623mm	1823mm	1933mm	2108mm	2450mm
Net Weight	960kg	1000kg	1910kg	2660kg	2860kg	3230kg	5000kg

We reserve the rights to change the specifications without prior notice

Shanghai Sailstar Machinery Group Co. Ltd.
1 Fengpu Avenue, Fengpu Industrial Zone,
201400 Shanghai, P.R.China



Tel: 86-21-67100168

Fax: 86-21-67100337

Email: info@sailstar.com.cn

Website: www.sailstar.com.cn