

Chest Heated Flatwork Ironer

C8-30-3R C8-33-3R C8-30-4R C8-33-4R



- One-piece chest and roll structure applies balanced pressure to flatwork
- High quality steam heated chest with large heating area
- Stainless steel gap piece with heating coils increases efficiency
- Powerful exhaust fan for fast moisture removal
- Variable speed frequency inverter drive
- Gradual speed increment between rolls for spreading effect
- High quality felt, spring system and float type steam trap
- User friendly computer control panel
- Four emergency stop buttons on each corner for safety
- Alarm system of steam and air pressure ensure smooth operation
- Individual pressure adjustment for left and right side improve ironing quality
- Chest isolated by Rockwool to prevent heat loss

Technical Specification:

	C8-30-3R	C8-33-3R	C8-30-4R	C8-33-4R
Number of Roll	3 rolls		4 rolls	
Maximum Ironing Width	3000mm	3300mm	3000mm	3300mm
Diameter of Roll	800mm		800mm	
Ironing Speed	4 - 40m/min		4 - 45m/min	
Steam Pressure	0.6 - 1.2Mpa		0.6 - 1.2Mpa	
Compressed Air Pressure	0.55 - 0.7Mpa		0.55 - 0.7Mpa	
Main Motor	15kw		15kw	
Frequency Inverter	15kw		15kw	
Exhaust Fan	3 x 1.5kw		4 x 1.5kw	
Air Flow	7500m³ /hr		10000m³ /hr	
Steam Inlet	DN65		DN65	
Steam Outlet	DN50		DN50	
Compressed Air	10mm		10mm	
Exhaust Duct	2 x 165mm		3 x 165mm	
Width	4200mm	4500mm	4200mm	4500mm
Depth	4700mm	4700mm	6005mm	6005mm
Height	2080mm	2080mm	2080mm	2080mm
Net Weight	9600kg	9900kg	12600kg	13000kg

We reserve the rights to change the specifications without prior notice

Shanghai Sailstar Machinery Group Co. Ltd. 1 Fengpu Avenue, Fengpu Industrial Zone, 201400 Shanghai, P.R.China



Tel: 86-21-67100168 Fax: 86-21-67100337

Email: <u>info@sailstar.com.cn</u>
Website: <u>www.sailstar.com.cn</u>