

Industrial Tilting Washer Extractor

MSM100T MSM150T MSM200T





- Air springs suspension system for stable high spin
- SS304 Stainless steel basket and outer drum
- Air bags actuated tilting system for one-way unloading tilt (Optional two-way tilt)
- Exclusive Tie Bar tilting security system
- Bearing Dry Zone design
- User friendly touch screen control
- Programmable computer up to 40 programs
- Programmable water levels, temperatures, cool-down
- Long lasting powder coated panels
- Large stainless steel door
- Automatic door opening with air seal
- Direct steam injection heating
- Safety door interlock system
- Five flushable detergent supply compartments
- Five liquid supply connection points
- Built-in bearing lubrication system
- Four sides safety skirt panel for full protection

Technical Specification:

	MSM100T	MSM150T	MSM200T
Rated Capacity	100kg	150kg	200kg
Basket Volume	1083L	1525L	2091L
Basket Diameter x Depth	1320mm x 791mm	1320mm x 1114mm	1626mm x 1007mm
Door Opening Diameter	850mm	850mm	1016mm
Motor	11kw	22kw	30kw
Inverter	15kw	22kw	37kw
High Extract G-force	320G	320G	320G
Water Inlet	DN40	DN40	DN50
Steam Inlet	DN40	DN40	DN40
Drain Connection	DN150	DN150	DN200
Compressed Air	14mm	14mm	14mm
Unloading Tilt Angle	14 degree	14 degree	14 degree
Loading Tilt Angle (Optional)	14 degree	14 degree	14 degree
Height (Tilt Position)	2202mm (2620mm)	2202mm (2690mm)	2500mm (2890mm)
Width x Depth	2032mm x 2470mm	2032mm x 2770mm	2327mm x 2820mm
Net Weight	5600kg	5900kg	8300kg

We reserve the rights to change the specifications without prior notice

Shanghai Sailstar Machinery Group Co. Ltd. 1 Fengpu Avenue, Fengpu Industrial Zone, 201400 Shanghai, P.R.China





Tel: 86-21-67100168 Fax: 86-21-67100337

Email: <u>info@sailstar.com.cn</u>
Website: <u>www.sailstar.com.cn</u>