

## PERC Dry Cleaning Machine

**P430 P440 P460 P480**



- Fully enclosed system with refrigeration recovery system maximize PERC recovery
- Programmable computer with self diagnostics, 6 automatic maintenance programs and up to 24 cleaning programs
- Three automatic self-cleaning tanks
- Two convertible ecological powder-less disc filters
- One double all-carbon filter
- Secondary carbon absorber system
- Button trap drying
- Automatic still waste removal system
- Still overflow preventer
- Double water separator
- Automatic still on/off
- Floor Safe safety trough
- Electronic drying controller to monitor solvent recovery
- Thermostatic controlled cooling water valve

### Technical Specification:

	P430	P440	P460	P480
Rated Capacity	14kg	18kg	27kg	36kg
Basket Volume	260L	340L	490L	640L
Basket Diameter x Depth	900mm x 410mm	960mm x 470mm	1050mm x 566mm	1180mm x 585mm
Door Opening Diameter	500mm	500mm	500mm	500mm
Tank Volume 1 / 2 / 3	144L / 144L / 125L	180L / 180L / 120L	200L / 200L / 160L	290L / 290L / 260L
Distillation Per Hour	150L/hr	210L/hr	285L/hr	310L/hr
Water Inlet	DN20	DN20	DN20	DN20
Steam In	DN15	DN15	DN15	DN15
Steam Out	DN15	DN15	DN15	DN15
Compressed Air	8mm	8mm	8mm	8mm
Height	2200mm	2140mm	2190mm	2600mm
Width	1470mm	2210mm	2260mm	2550mm
Depth	2255mm	1630mm	1800mm	1960mm
Net Weight	1350kg	2240kg	2790kg	3350kg

We reserve the rights to change the specifications without prior notice

**Shanghai Sailstar Machinery Group Co. Ltd.**  
**1 Fengpu Avenue, Fengpu Industrial Zone,**  
**201400 Shanghai, P.R.China**



**Tel: 86-21-67100168**

**Fax: 86-21-67100337**

**Email: [info@sailstar.com.cn](mailto:info@sailstar.com.cn)**

**Website: [www.sailstar.com.cn](http://www.sailstar.com.cn)**