

Soft Mount Washer Extractor

SS 17 SS23



- Compact design for space saving
- Suspension system with springs and shock absorbers
- Frequency inverter drive up to 300G
- Programmable computer control up to 15 wash programs
- Programmable water levels and water temperature
- Patented safety door interlock system
- Stainless steel door with large sight glass
- Stainless steel basket, outer shell, front and top panels
- All electromagnetic operated valves eliminate need of compressed air
- Three flushable compartment dry supply injectors
- Standard hot and cold water inlets
- Direct steam injection heating OR electrical heating

Technical Specification:

	SS17		SS23	
Rated Capacity	17kg		23kg	
Heating Mode	Steam	Electric	Steam	Electric
Basket Volume	170L		230L	
Basket Diameter x Depth	706mm x 435mm		706mm x 580mm	
Door Opening Diameter	400mm		400mm	
High Extract Speed	872rpm		872rpm	
High Extract G-Force	300G		300G	
Motor	1.5kw		2.2kw	
Inverter	2.2kw		3.7kw	
Electrical Heating	-	18kw	-	18kw
Water inlet	DN20		DN20	
Steam inlet	DN15	-	DN15	-
Drain connection	DN76		DN76	
Height	1348mm		1348mm	
Width	920mm		920mm	
Depth	906mm		1051mm	
Net weight	636kg		710kg	

We reserve the rights to change the specifications without prior notice

Shanghai Sailstar Machinery Group Co. Ltd.
1 Fengpu Avenue, Fengpu Industrial Zone,
201400 Shanghai, P.R.China



Tel: 86-21-67100168

Fax: 86-21-67100337

Email: info@sailstar.com.cn

Website: www.sailstar.com.cn